

# 3/4" x 25' and 5/8" x 25' Pipe Slings



**COMMON USES:** *Transporting and moving of cylindrical smooth wall pipe.*

## SPECIFICATIONS

- Tiger pipe slings are built to ASME B30.9 specifications.
- 50 Slings to a rack
- Slings are pull tested every 12 months
- Visual inspection between each rental
- Test certificates available 24/7

## RACK SPECIFICATIONS:

- Est. Tare Weight: 1,000 lbs. [454 KG]
- Max Gross Weight: 4,000 lbs. [1,814 KG]
- Pay Load Weight: 3,000 lbs. [1,361 KG]
- Length: 2,540 mm [100"][8'4"]
- Width: 1,062 mm [42"][3'6"]
- Height: 1,143 mm [45"][3'9"]



## Sling & Rigging Management Program

### COMPLIANCE IS THE FIRST STEP TO SUCCESS

- The safest compliance management program for lifting slings and rigging covering dockside locations, drilling rigs and production facilities; complying with API RP-75 safe practices.
- Confidence in the event of a BESSE audit.
- Reduce liability exposure on your facility.
- Protect Life & Assets.

### EQUIPMENT

- Nylon slings: 2, 4 & 6 part lifting assemblies, shackles, come-a-longs, and chain falls.
- 1st and 2nd inventory packages will be all new equipment. 3rd and 4th packages will consist of re-certified equipment. All equipment discarded after the completion of the two year cycles.
- All equipment will have individual serial #'s assigned for traceability and documentation.
- All equipment will be color coded different for every package.

### DOCUMENTATION

- All equipment tested two times the maximum load capacity at date of manufacture with testing certification.
- PDF Electronic and hard copy documentation provided
- Complete traceability of all equipment, returned damaged and expired.



TIGER 8' X 20' DNV 2.7-1 OFFSHORE CONTAINER LOADED WITH SLINGS & RIGGING



**Make it happen.**

[www.TigerOffshoreRentals.com](http://www.TigerOffshoreRentals.com) | 24/7 Dispatch 1.877.844.3791