100 BBL USCG APPROVED MARINE PORTABLE TANK (MPT)



COMMON USES

The 100 BBL MPT fluid tank can be used for produced water processing, pipeline flushing tankage, waste oil collection, drilling mud transfer and much more.





▶ TECHNICAL DATA

DIMENSIONS	LXWXH	
EXTERNAL (MM)	4343 x 2438 x 3150	
EXTERNAL (FT)	14'3" x 8' x 10'4"	
WEIGHT	KGS	LBS
TARE	4318	9520
PAYLOAD	20629	45480
MAX GROSS WEIGHT (MGW)	24947	55000
CAPACITY	LITERS	GALS
VOLUME	15899	4200

ADDITIONAL FEATURES

FRAME

- Designed for Offshore Dynamic Lifting in Accordance with API RP 2A / USCG
- Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder and Four Point Lift System


VESSEL

- · Carbon Steel
- 20" Manway, 3" Male Camlock with Cap, Pressure & Vacuum Relief Vent Flow Rate of 4208 Cubic Ft. of Free Air per Minute as per CFR 49, 178.270-11
- Set at 25 PSI/6" Vacuum
- · Work Pressure: 26 PSI
- · Test Pressure: 39 PSI
- External Pressure: 7.5 PSI
- Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat
- · Interior Coatings: High-Build Epoxy Lining System

DRAWINGS

SIDE VIEW

4343 mm [171"] [14'3"]



FRONT VIEW

2438 mm [96"] [8']

