

# 250 BBL CGA TRANSPORT TANK



## ▶ COMMON USES

The 250 bbl CGA Transport Tank provides secure transportation and storage of drilling, production and completion fluids as well as fuel, waste and other liquids.



## ▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM) RAILS DOWN		9195 x 2591 x 3200	
EXTERNAL (FT) RAILS DOWN		30'2" x 8'6" x 10'6"	
EXTERNAL (MM) RAILS UP		9195 x 2591 x 4064	
EXTERNAL (FT) RAILS UP		30'2" x 8'6" x 13'4"	
WEIGHT		KGS	LBS
TARE		9979	22000
PAYLOAD		103419	228000
MAX GROSS WEIGHT (MGW)		113398	250000
CAPACITY		LITERS	GALS
VOLUME		39747	10500

### ADDITIONAL FEATURES

#### FRAME

- Designed for Offshore Dynamic Lifting in Accordance with API RP 2A & SEPCo OPS 0055
- Steel Frame, Two 20" Top Mounted Manways with Ladders, Two Point Lift System (Empty Lift Only) and Eight Skid Mounted Weld Downs

#### VESSEL

- Designed and Constructed in Accordance with Marine Safety Manual, Chapter 11, Section F, Carriage of Combustible and Flammable Cargo, Independent Tanks
- One 4" Suction/Drain with 4" Butterfly Valve with Male Camlock & Cap, One 4" Offset Circulation Line 4" with Butterfly Valve with Female Camlock & Plug and One 4" Fill Line with 4" Butterfly Valve with Female Camlock & Plug
- Maximum Working Pressure 18 PSI
- Two 3" Atmospheric Vents, One 30" Manway/Cleanout and One Center Baffle
- Exterior Coating: Three Part Poly
- Interior Coating: High Build Chemical Resistant Liner

## ▶ DRAWINGS

