

25 BBL ELECTRIC BLENDING UNIT



▶ COMMON USES

The 25 bbl Electric Blending Unit is designed to mix mud for drilling operations. Also used for tank bottom reductions and tank cleaning for the industrial market.



▶ TECHNICAL DATA

| DIMENSIONS | | L X W X H | |
|---------------|--|--------------------|------|
| EXTERNAL (MM) | | 3860 x 2438 x 2972 | |
| EXTERNAL (FT) | | 12'8" x 8' x 9'9" | |
| WEIGHT | | KGS | LBS |
| EMPTY WEIGHT | | 3538 | 7800 |
| CAPACITY | | LITERS | GALS |
| VOLUME | | 3975 | 1050 |

ADDITIONAL FEATURES

FRAME

- Designed for Offshore Dynamic Lifting in Accordance with API RR 2A
- Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder, OSHA Compliant Hand Rails and Four Point Lift System
- Work Platform For Easy Access to Palletized Material

VESSEL

- Meets Class I DIV II Requirements
- 10 HP Variable Speed Blender (up to 60 RPM)
- 40 HP 4"x 5" Electric Centrifugal Pump
- 4" Suction Line, 4" Fill Line, 4" Circulation Line and 3" Portable Tank Fill Line (Rota-Table)
- Work Deck for Palletized Material with Swing Doors
- Explosion-Proof Work Lights

▶ DRAWINGS

