

# 500 BBL CGA TRANSPORT TANK



## ▶ COMMON USES

The 500 bbl CGA Transport Tank provides secure transportation and storage of drilling, production and completion fluids as well as fuel, waste and other liquids.



## ▶ TECHNICAL DATA

DIMENSIONS	L X W X H	
EXTERNAL HAND RAILS DOWN (MM)	12700 x 2591 x 3658	
EXTERNAL HAND RAILS DOWN (FT)	41'8" x 8'6" x 12'	
EXTERNAL HAND RAILS UP (MM)	12700 x 2591 x 4521	
EXTERNAL HAND RAILS UP (FT)	41'8" x 8'6" x 14'10"	
WEIGHT	KGS	LBS
TARE	16783	37000
PAYLOAD	210013	463000
MAX GROSS WEIGHT (MGW)	226796	500000
CAPACITY	LITERS	GALS
VOLUME	79494	21000

### ADDITIONAL FEATURES

#### FRAME

- Designed for Offshore Dynamic Lifting in Accordance with API RP 2A & SEPCo OPS 0055
- Steel Frame, Two 20" Top Mounted Manways with Hand Rails, Ladder, Two Point Lift System (Empty Lift Only) and Eight Skid Mounted Weld Downs

#### VESSEL

- Designed and Constructed in Accordance with Marine Safety Manual, Chapter 11, Section F, Carriage of Combustible and Flammable Cargo, Independent Tanks
- One 4" Suction/Drain with 4" Butterfly Valve with Male Camlock & Cap, One 4" Offset Circulation Line 4" with Butterfly Valve with Female Camlock & Plug and One 4" Fill Line with 4" Butterfly Valve with Female Camlock & Plug
- Maximum Working Pressure 18 PSI
- Two 3" Atmospheric Vents, One 30" Manway/Cleanout and Two Equally Spaced Baffles
- Exterior Coating: Three Part Poly
- Interior Coating: High Build Chemical Resistant Liner

## ▶ DRAWINGS

