

DNV 25 BBL STAINLESS STEEL LOW PROFILE VERTICAL TANK



▶ COMMON USES

The DNV 25 bbl SS Low Profile Vertical Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.



▶ TECHNICAL DATA

DIMENSIONS	L X W X H	
EXTERNAL (MM)	2268 x 2268 x 2500	
EXTERNAL (FT)	7'5" x 7'5" x 8'2"	
WEIGHT	KGS	LBS
TARE	2400	5291
PAYLOAD	7600	16755
MAX GROSS WEIGHT (MGW)	10000	22046
CAPACITY	LITERS	GALS
VOLUME	3975	1050

ADDITIONAL FEATURES

FRAME

- Designed, Constructed, Tested to EN12079-1 / DNV 2.7-1 IMDG, ASME VIII Div. 1
- Steel Tubing Frame, Forklift Pockets on All Four Sides, Built in Ladder, Four Point Lift System and Stackable - 3 High Empty, 2 High Full

VESSEL

- Design: ASME VIII Div 1 2.67 Bar (38.7 PSI) WP 4.0 Bar (58 PSI) TP
- 316L Stainless Steel; Design Temp: (-20°C to + 55°C)
- Inner Diameter: 2,000 mm = 78.75"
- Manhole Diameter: 500 mm = 19.69"
- Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat

▶ DRAWINGS

