

DNV 550 GALLON ACID TANK



▶ COMMON USES

The DNV 550 Gallon Acid Tank is used to safely move hazardous fluids offshore. Designed for corrosives, acids and solvents that are compatible with polyethylene. This is a dependable and versatile package for the Offshore E&P Industry.



▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)		2422 x 1584 x 1912	
EXTERNAL (FT)		7'11" x 5'2" x 6'3"	
WEIGHT		KGS	LBS
TARE		1460	3220
PAYLOAD		2900	6390
MAX GROSS WEIGHT (MGW)		4360	9610
CAPACITY		LITERS	GALS
VOLUME		2082	550

ADDITIONAL FEATURES

FRAME

- Designed, Constructed, Tested to EN12079-1 / DNV 2.7-1
- Steel Tubing Frame, Stackable and Forklift Pockets on all Four Sides

VESSEL

- UN/DOT Certified (31H2)
- Packaging Group II & III per Title 49 CFR
- 1/2" Rotationally Molded Polyethylene
- 1/2" Wall Thickness, HDPE Linear
- 1.9 Specific Gravity
- Two 2" Bungs, One in Tank Top and One in Tank Lid
- 2" Plastic Vacuum Relief Vent
- 6.5" Heavy-Duty Fill Cap with Tether
- 2" Full Port Bottom Drain Valve with Dust Cap
- Molded-in and Inked Gallon Markers

▶ DRAWINGS

