



# 25 BBL ELECTRIC BLENDING UNIT

## ▶ COMMON USES

The 25 bbl Electric Blending Unit is designed to mix mud for drilling operations. Also used for tank bottom reductions and tank cleaning for the industrial market.

## ▶ TECHNICAL DATA

DIMENSIONS	L X W X H	
EXTERNAL (MM)	3860 x 2438 x 2972	
EXTERNAL (FT)	12'8" x 8' x 9'9"	
WEIGHT	KGS	LBS
EMPTY WEIGHT	3538	7800
CAPACITY	LITERS	GALS
VOLUME	3975	1050
ADDITIONAL FEATURES		
<b>FRAME</b>		
<ul style="list-style-type: none"> <li>• Designed for Offshore Dynamic Lifting in Accordance with API RR 2A</li> <li>• Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder, OSHA Compliant Hand Rails and Four Point Lift System</li> <li>• Work Platform For Easy Access to Palletized Material</li> </ul>		
<b>VESSEL</b>		
<ul style="list-style-type: none"> <li>• Meets Class I DIV II Requirements</li> <li>• 10 HP Variable Speed Blender (up to 60 RPM)</li> <li>• 40 HP 4"x 5" Electric Centrifugal Pump</li> <li>• 4" Suction Line, 4" Fill Line, 4" Circulation Line and 3" Portable Tank Fill Line (Rota-Table)</li> <li>• Work Deck for Palletized Material with Swing Doors</li> <li>• Explosion-Proof Work Lights</li> </ul>		



## ▶ DRAWINGS

