



# 500 BBL CGA TRANSPORT TANK

## ▶ COMMON USES

The 500 bbl CGA Transport Tank provides secure transportation and storage of drilling, production and completion fluids as well as fuel, waste and other liquids.

## ▶ TECHNICAL DATA

DIMENSIONS	L X W X H	
EXTERNAL HAND RAILS DOWN (MM)	12700 x 2591 x 3658	
EXTERNAL HAND RAILS DOWN (FT)	41'8" x 8'6" x 12'	
EXTERNAL HAND RAILS UP (MM)	12700 x 2591 x 4521	
EXTERNAL HAND RAILS UP (FT)	41'8" x 8'6" x 14'10"	
WEIGHT	KGS	LBS
TARE	16783	37000
PAYLOAD	210013	463000
MAX GROSS WEIGHT (MGW)	226796	500000
CAPACITY	LITERS	GALS
VOLUME	79494	21000
ADDITIONAL FEATURES		
<b>FRAME</b>		
<ul style="list-style-type: none"> <li>• Designed for Offshore Dynamic Lifting in Accordance with API RP 2A &amp; SEPCo OPS 0055</li> <li>• Steel Frame, Two 20" Top Mounted Manways with Hand Rails, Ladder, Two Point Lift System (Empty Lift Only) &amp; Eight Skid Mounted Weld Downs</li> </ul>		
<b>VESSEL</b>		
<ul style="list-style-type: none"> <li>• Designed and Constructed in Accordance with Marine Safety Manual, Chapter 11, Section F, Carriage of Combustible and Flammable Cargo, Independent Tanks</li> <li>• One 4" Suction/Drain with 4" Butterfly Valve with Male Camlock &amp; Cap, One 4" Offset Circulation Line 4" with Butterfly Valve with Female Camlock &amp; Plug and One 4" Fill Line with 4" Butterfly Valve with Female Camlock &amp; Plug</li> <li>• Maximum Working Pressure 18 PSI</li> <li>• Two 3" Atmospheric Vents, One 30" Manway/Cleanout and Two Equally Spaced Baffles</li> <li>• Exterior Coating: Three Part Poly</li> <li>• Interior Coating: High Build Chemical Resistant Liner</li> </ul>		



## ▶ DRAWINGS

