



50 BBL ISO TRANSPORT TANK

▶ COMMON USES

The DNV 50 bbl ISO Transport Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.

▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)	2997 x 2438 x 2438		
EXTERNAL (FT)	9'10" x 8' x 8'		
WEIGHT		KGS	LBS
TARE	1920	4232	
PAYLOAD	13080	28837	
MAX GROSS WEIGHT (MGW)	15000	33069	
CAPACITY		LITERS	GALS
VOLUME	7950	2100	
ADDITIONAL FEATURES			
FRAME			
<ul style="list-style-type: none"> Designed for Offshore Dynamic Lifting in Accordance with API RR 2A & SEPCo OPS 0055 			
VESSEL			
<ul style="list-style-type: none"> 316L Stainless Steel Working Pressure.: 4 Bar - 58PSI Test Pressure.: 6 Bar - 87 PSI Manhole: 20" Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat 			



▶ DRAWINGS

