



DNV 125 BBL STAINLESS STEEL TRANSPORT TANK

▶ COMMON USES

The DNV 125 bbl SS Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.

▶ TECHNICAL DATA

DIMENSIONS	L X W X H	
EXTERNAL (MM)	6058 x 2438 x 2591	
EXTERNAL (FT)	20' x 8' x 8'6"	
WEIGHT	KGS	LBS
TARE	7300	16095
PAYLOAD	22700	50045
MAX GROSS WEIGHT (MGW)	30000	66140
WEIGHT - DNV MAX LIMIT	KGS	LBS
TARE	7300	16095
PAYLOAD	17700	39022
MAX GROSS WEIGHT (MGW)	25000	55117
CAPACITY	LITERS	GALS
VOLUME	20000	5285

ADDITIONAL FEATURES

FRAME

- Designed, Constructed, Tested to EN12079-1, DNV 2.7-1, SEPCo OPS 0055
- Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder, Four Point Lift System and Stackable - 3 High Empty, 2 High Full
- Equipped with a Retractable Fall Protection Anchorage Rod

VESSEL

- ASME VIII DIV 1, T11 UN Portable Tank, IMDG, IMO 860, US/DOT & UK DFT
- ISO - 1493-3:1995 with CSC Safety Approval Plate for 8'x20' Container
- 316L Stainless Steel
- Test Pressure: 6 BAR - 87 PSI; Working Pressure: 4 BAR - 58 PSI
- Tank Design Temperature is -40°C; Frame Design Temperature is -20°C
- 20" Hatch; One 4" Discharge Valve; Three-Way Discharge Closure Valve
- Equipped with Separate Valve for Drawing Sample of Tank Contents
- Level Gauge Included to Monitor Fluid Levels
- Capable of Venting Air at Ground Level by Way of Control Handle



▶ DRAWINGS

