



# DNV 25 BBL STAINLESS STEEL LOW PROFILE VERTICAL TANK

## ▶ COMMON USES

The DNV 25 bbl SS Low Profile Vertical Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.

## ▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)	2268 x 2268 x 2500		
EXTERNAL (FT)	7'5" x 7'5" x 8'2"		
WEIGHT		KGS	LBS
TARE	2400	5291	
PAYLOAD	7600	16755	
MAX GROSS WEIGHT (MGW)	10000	22046	
CAPACITY		LITERS	GALS
VOLUME	3975	1050	
ADDITIONAL FEATURES			
<b>FRAME</b>			
<ul style="list-style-type: none"> <li>• Designed, Constructed, Tested to EN12079-1 / DNV 2.7-1 IMDG, ASME VIII Div. 1</li> <li>• Steel Tubing Frame, Forklift Pockets on All Four Sides, Built in Ladder, Four Point Lift System and Stackable - 3 High Empty, 2 High Full</li> </ul>			
<b>VESSEL</b>			
<ul style="list-style-type: none"> <li>• Design: ASME VIII Div 1 2.67 Bar (38.7 PSI) WP 4.0 Bar (58 PSI) TP</li> <li>• 316L Stainless Steel; Design Temp: (-20°C to + 55°C)</li> <li>• Inner Diameter: 2,000 mm = 78.75"</li> <li>• Manhole Diameter: 500 mm = 19.69"</li> <li>• Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat</li> </ul>			



## ▶ DRAWINGS

