



# DNV 47.5 BBL STAINLESS STEEL TANK

## ▶ COMMON USES

The DNV 47.5 bbl SS Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.

## ▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)	2991 x 2438 x 2591		
EXTERNAL (FT)	9'10" x 8' x 8'6"		
WEIGHT		KGS	LBS
TARE	2650	5842	
PAYLOAD	12350	27227	
MAX GROSS WEIGHT (MGW)	15000	33119	
CAPACITY		LITERS	GALS
VOLUME	7640	2018	
ADDITIONAL FEATURES			
<b>FRAME</b>			
<ul style="list-style-type: none"> <li>• Designed, Constructed, Tested to EN12079-1 / DNV 2.7-1 IMDG, ASME VIII Div. 1</li> <li>• Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder, Four Point Lift System and Stackable - 3 High Empty, 2 High Full</li> <li>• Equipped with a Retractable Fall Protection Anchorage Rod</li> </ul>			
<b>VESSEL</b>			
<ul style="list-style-type: none"> <li>• Design: ASME VIII Div 1 [NCS] / T11 UN Portable Tank / IMDG - Rid/ADR</li> <li>• 316L Stainless Steel</li> <li>• Level Gauge Included to Monitor Fluid Levels</li> <li>• Capable of Venting Air at Ground Level by Way of Control Handle</li> <li>• Test Pressure: 6 Bar - 87 PSI</li> <li>• Working Pressure: 4 Bar - 58 PSI</li> <li>• ISO Corner - 8' X 10' with CSC Safety Approval Plate</li> <li>• One 3" Discharge Valve with Three-Way Closure</li> <li>• 20" Top Hatch</li> </ul>			



## ▶ DRAWINGS

