



DNV 550 GALLON ACID TANK

▶ COMMON USES

The DNV 550 Gallon Acid Tank is used to safely move hazardous fluids offshore. Designed for corrosives, acids and solvents that are compatible with polyethylene. This is a dependable and versatile package for the Offshore E&P Industry.

▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)	2422 x 1584 x 1912		
EXTERNAL (FT)	7'11" x 5'2" x 6'3"		
WEIGHT		KGS	LBS
TARE	1460	3220	
PAYLOAD	2900	6390	
MAX GROSS WEIGHT (MGW)	4360	9610	
CAPACITY		LITERS	GALS
VOLUME	2082	550	
ADDITIONAL FEATURES			
FRAME			
<ul style="list-style-type: none"> • Designed, Constructed, Tested to EN12079-1 / DNV 2.7-1 • Steel Tubing Frame, Stackable and Forklift Pockets on all Four Sides 			
VESSEL			
<ul style="list-style-type: none"> • UN/DOT Certified (31H2) • Packaging Group II & III per Title 49 CFR • 1/2" Rotationally Moulded Polyethylene • 1/2" Wall Thickness, HDPE Linear • 1.9 Specific Gravity • Two 2" Bungs, One in Tank Top and One in Tank Lid • 2" Plastic Vacuum Relief Vent • 6.5" Heavy-Duty Fill Cap with Tether • 2" Full Port Bottom Drain Valve with Dust Cap • Molded-in and Inked Gallon Markers 			



▶ DRAWINGS

