



100 BBL USCG APPROVED MARINE PORTABLE TANK (MPT)

► COMMON USES

The 100 BBL MPT fluid tank can be used for produced water processing, pipeline flushing tankage, waste oil collection, drilling mud transfer and much more.

► TECHNICAL DATA

| DIMENSIONS | L X W X H | |
|--|--------------------|-------|
| EXTERNAL (MM) | 4343 x 2438 x 3150 | |
| EXTERNAL (FT) | 14'3" x 8' x 10'4" | |
| WEIGHT | KGS | LBS |
| TARE | 4318 | 9520 |
| PAYLOAD | 20629 | 45480 |
| MAX GROSS WEIGHT (MGW) | 24947 | 55000 |
| CAPACITY | LITERS | GALS |
| VOLUME | 15899 | 4200 |
| ADDITIONAL FEATURES | | |
| FRAME | | |
| <ul style="list-style-type: none"> Designed for Offshore Dynamic Lifting in Accordance with API RP 2A / USCG Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder and Four Point Lift System | | |
| VESSEL | | |
| <ul style="list-style-type: none"> Carbon Steel 20" Manway, 3" Male Camlock with Cap, Pressure & Vacuum Relief Vent Flow Rate of 4208 Cubic Ft. of Free Air per Minute as per CFR 49, 178.270-11 Set at 25 PSI/6" Vacuum Work Pressure: 26 PSI Test Pressure: 39 PSI External Pressure: 7.5 PSI Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat Interior Coatings: High-Build Epoxy Lining System | | |



► DRAWINGS

