

25 BBL MARINE PORTABLE TANK (MPT)

COMMON USES

25 bbl Marine Portable Tank is used for secure transportation and storage of drilling, production and completion fluids as well as fuel, waste and other liquids.

TECHNICAL DATA

DIMENSIONS	LXWXH	
EXTERNAL (MM)	2438 x 1727 x 2248	
EXTERNAL (FT)	8' x 5'8" x 7'5"	
WEIGHT	KGS	LBS
TARE	1950	4300
PAYLOAD	9389	20700
MAX GROSS WEIGHT (MGW)	11339	25000
CAPACITY	LITERS	GALS
VOLUME	3975	1050

ADDITIONAL FEATURES

FRAME

- Designed for Offshore Dynamic Lifting in Accordance with API RR 2A & SEPCo OPS 0055 / USCG
- Steel Tubing Frame, Forklift Pockets on Both Sides, Four Point Lift System and Stackable - 3 High Empty, 2 High Full

VESSEL

- Constructed with 5/16" SA-36 Plate, GR 70 Pl Heads. 2.5" PRV Vent (31 PSI) with 2" Zook Flange Mounted Burst Plate, 20" Manway, 3" Male Camlock with Cap
- Test Pressure 38.6 PSI; Maximum Working Pressure 25PSI/6"; Vacuum Maximum Temperature 200°F
- · Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat
- · Interior Coatings: High-Build Epoxy Lining System





DRAWINGS

2438 mm [96"] [8']

SIDE VIEW

1727 mm [68"] [5'8"]

FRONT VIEW