



50 BBL ISO TRANSPORT TANK

COMMON USES

The 50 bbl ISO Transport Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.

TECHNICAL DATA

| DIMENSIONS | L X W X H | |
|--|--------------------|-------|
| EXTERNAL (MM) | 2997 x 2438 x 2438 | |
| EXTERNAL (FT) | 9'10" x 8' x 8' | |
| WEIGHT | KGS | LBS |
| TARE | 1920 | 4232 |
| PAYLOAD | 13080 | 28837 |
| MAX GROSS WEIGHT (MGW) | 15000 | 33069 |
| CAPACITY | LITERS | GALS |
| VOLUME | 7950 | 2100 |
| ADDITIONAL FEATURES | | |
| FRAME | | |
| <ul style="list-style-type: none"> Designed for Offshore Dynamic Lifting in Accordance with API RR 2A & SEPCo OPS 0055 | | |
| VESSEL | | |
| <ul style="list-style-type: none"> 316L Stainless Steel Working Pressure.: 4 Bar - 58PSI Test Pressure.: 6 Bar - 87 PSI Manhole: 20" Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat | | |



DRAWINGS

