



DNV 25 BBL STAINLESS STEEL LOW PROFILE VERTICAL TANK

► COMMON USES

The DNV 25 bbl SS Low Profile Vertical Tank is built for safely moving hazardous fluids offshore. Designed for drilling, completion, production, P&A and work over fluids that are compatible with 316L Stainless Steel. This package is dependable and versatile for the Offshore E&P Industry.

► TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)		2268 x 2268 x 2500	
EXTERNAL (FT)		7'5" x 7'5" x 8'2"	
WEIGHT		KGS	LBS
TARE		2400	5291
PAYLOAD		7600	16755
MAX GROSS WEIGHT (MGW)		10000	22046
CAPACITY		LITERS	GALS
VOLUME		3975	1050
ADDITIONAL FEATURES			
FRAME			
<ul style="list-style-type: none"> Designed, Constructed, Tested to EN12079-1 / DNV 2.7-1 IMDG, ASME VIII Div. 1 Steel Tubing Frame, Forklift Pockets on All Four Sides, Built in Ladder, Four Point Lift System and Stackable - 3 High Empty, 2 High Full 			
VESSEL			
<ul style="list-style-type: none"> Design: ASME VIII Div 1 2.67 Bar (38.7 PSI) WP 4.0 Bar (58 PSI) TP 316L Stainless Steel; Design Temp: (-20° C to + 55° C) Inner Diameter: 2,000 mm = 78.75" Manhole Diameter: 500 mm = 19.69" Exterior Coatings: Zinc Rich Epoxy Primer, Polyurethane Top Coat 			



► DRAWINGS

